

# NK-HiQ™

## CNS REMOTE CLIENT



### Smart

- One admit, one discharge – patient data flows seamlessly and securely throughout the enterprise
- Flexible monitoring with patient tile customization and device assignment capability
- Simplified and improved workflow with Send to EMR support
- Electronic ECG snippet documentation on NK-HiQ™ CNS Remote Client\* can help clinical users save time and paper

### Safe

- Intuitive, real-time management of monitored data from locations other than the Life Scope® Central Station
- Display of wandering and fall detection icons generated by wearable monitors
- Expanded data review capability

### Secure

- Microsoft Windows® 10 secure operating system
- Comprehensive integration with hospital enterprise system
- Software upgrades and security updates included

\* Used for secondary monitoring

# NK-HiQ™ CNS REMOTE CLIENT SPECIFICATIONS

## DISPLAY

<b>Size/Type</b>	24" color LED display
<b>Resolution</b>	HD 1920 x 1080
<b>Number of Patients</b>	4, 6, 8, 10, 12 or 16 patients per display
<b>Waveform Display Items (Based on Connected Monitor/Transmitter)</b>	ECG (up to 12 vectors), IBP (1-8), respiration wave, pulse (SpO <sub>2</sub> ), EEG (1-2), FLOW/Paw, CO <sub>2</sub> , external input, anesthetic gas (O <sub>2</sub> , CO <sub>2</sub> , N <sub>2</sub> O, agent)
<b>Number of Traces, All Beds Screen</b>	Up to 32 per display; number of traces per patient is based on number of patients displayed
<b>Number of Traces, Individual Bed Screen</b>	Up to 16
<b>Waveform Sweep Speed</b>	25 mm/s, 50 mm/s, 6.25 mm/s (respiration measurement)
<b>Alphanumeric Display Items (Based on Connected Monitor/Transmitter)</b>	Heart rate, pulse rate, VPC rate, respiration rate, ST level, IBP (systolic, diastolic, mean), SpO <sub>2</sub> , CO <sub>2</sub> , cardiac output, blood temperature, CCO, CCO<Tb>, CCI, NIBP (systolic, diastolic, mean), temperature, SvO <sub>2</sub> , PICCO, FLOW/Paw, N <sub>2</sub> O, O <sub>2</sub> , agent, BIS, tcPO <sub>2</sub> , tcPCO <sub>2</sub> , TV, MV, PEEP, etc.

## ALARMS

<b>Alarm Type</b>	Crisis, warning, advisory, technical
<b>Alarm Items (Depends on Connected Monitor/Transmitter)</b>	Vital signs: Heart rate, pulse rate, respiration rate, apnea, ST level, IBP (systolic, diastolic, and mean), NIBP (systolic, diastolic, and mean), temperature, Delta T, Tb, SpO <sub>2</sub> , SvO <sub>2</sub> , CCO, ventilator, anesthetic gas, BIS, EtCO <sub>2</sub> , FICO <sub>2</sub> , EtO <sub>2</sub> , FIO <sub>2</sub> , N <sub>2</sub> O, O <sub>2</sub> , tcPO <sub>2</sub> , tcPCO <sub>2</sub> , MV, Ppeak, PEEP  Arrhythmia: asystole, v-fib, ext. tachycardia, ext. bradycardia, v-tach, tachycardia, bradycardia, VPC run, couplet, early VPC, multiform, bigeminy, freq. VPC, prolonged R-R interval
<b>Alarm Display</b>	Flashing bed frame, highlighted numerical display, highlighted alarm message
<b>Alarm Icon/Arrhythmia Icon</b>	Available when vital sign alarm, technical alarm, or arrhythmia occurs

## OVERVIEW FUNCTION

Displays user-selectable vital signs, up to 12 ECG waveforms, reviews, alarm events, and status messages associated with the selected overview bed. The overview bed can be any bed in the network that the RNS is not monitoring.

## THERMAL ARRAY RECORDER, WS-960P (OPTION)

<b>Recording Method</b>	Thermal array recording
<b>Number of Waveforms</b>	3
<b>Paper Speed</b>	25 mm/sec
<b>Type of Recording</b>	Manual, alarm, periodic, remote

## NETWORK LASER PRINTER (OPTION)

### HP LaserJet M608dn or Equivalent (Postscript Printer)

<b>Number of Waveforms</b>	Up to 16
<b>Type of Recording</b>	Manual, periodic

## RNS-6803 ALL-IN-ONE COMPUTER

<b>Dimensions (w/o stand)</b>	13.5" H x 21.3" W x 2.1" D
<b>Weight</b>	18.6 lbs
<b>Power Consumption</b>	100-240 VAC, 47-63 Hz, maximum 3.6A (low AC range)/maximum 1.8A (high AC range)
<b>Operating Temperature</b>	32°F to 95°F (0°C to 35°C)
<b>Operating Humidity</b>	20% to 80%, non-condensing
<b>Storage Temperature</b>	-40°F to 149°F (-40°C to 65°C)
<b>Storage Humidity</b>	20% - 80%, non-condensing



For more information, please contact us at 1-800-325-0283 or visit [us.nihonkohden.com](http://us.nihonkohden.com)



NK-HiQ is a trademark of Nihon Kohden Corporation.  
Life Scope is a registered trademark of Nihon Kohden.  
Windows is a registered trademark of Microsoft Corporation.  
Exceptional Solutions, Simply Delivered is a trademark of Nihon Kohden.



Exceptional Solutions,  
Simply Delivered.™

MMLB 197 D CO-2692